

## LED Lima

- NEW: Available as wireless Smart Lighting solution (BLE)
- Stylish linear luminaire suitable for surface mounting and suspended use
- Suitable for use in office
- Available in 1200 & 1500mm length
- Suspension kit including transparent cable as accessory
- Connection kit accessory to create continuous lines available
- DALI or Smart Lighting (BLE) dimmable



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	UGR	CCT (K)	Weight (kg/pc)
542005000500	LEDLima L12-15W-3000-U19-DALI	TL 1x28W	15	1725	110	19	3000	2.55
542005000600	LEDLima L12-15W-4000-U19-DALI	TL 1x28W	15	1800	115	19	4000	2.55
542005000700	LEDLima L15-18W-3000-U19-DALI	TL 1x35W	18	2070	110	19	3000	3.08
542005000800	LEDLima L15-18W-4000-U19-DALI	TL 1x35W	18	2160	115	19	4000	3.08
542005001300	LEDLima L12-30W-3000-DALI	TL 1x54W	30	3300	110	22	3000	2.55
542005001400	LEDLima L12-30W-4000-DALI	TL 1x54W	30	3450	115	22	4000	2.55
542005001500	LEDLima L15-36W-3000-DALI	TL 1x80W	36	3960	110	22	3000	3.08
542005001600	LEDLima L15-36W-4000-DALI	TL 1x80W	36	4140	115	22	4000	3.08
542005004900	LEDLima L12-15W-3000-U19-BLE	TL 1x28W	15	1725	110	19	3000	2.55
542005004800	LEDLima L12-15W-4000-U19-BLE	TL 1x28W	15	1800	115	19	4000	2.55
542005004700	LEDLima L15-18W-3000-U19-BLE	TL 1x35W	18	2070	110	19	3000	3.08
542005004600	LEDLima L15-18W-4000-U19-BLE	TL 1x35W	18	2160	115	19	4000	3.08
542005004500	LEDLima L12-30W-3000-BLE	TL 1x54W	30	3300	110	22	3000	2.55
542005004400	LEDLima L12-30W-4000-BLE	TL 1x54W	30	3450	115	22	4000	2.55
542005004300	LEDLima L15-36W-3000-BLE	TL 1x80W	36	3960	110	22	3000	3.08
542005004200	LEDLima L15-36W-4000-BLE	TL 1x80W	36	4140	115	22	4000	3.08

Emergency lighting available on request.

## Accessories



599006009000  
LEDLima Suspension-Kit



599006008900  
LEDLima Connection-Kit

### Technical Specifications

Lifespan (L70B50)	70,000 h
Lifespan (L80B50)	50,000 h
On-/Off-cycles	100,000
Dimmable	Yes (DALI/BLE)
Beam angle	70 °
Finishing	Aluminum
Colour rendering index CRI	≥ 80
Degree of protection (IP)	IP20
Impact strength	IK02
Protection class	I
Risk group	RG0
Control gear included	Yes
Glow wire test	650 °C
Driver failure rate (at 5,000 hrs)	1 %
Power factor	≥ 0.90

### Electrical Supply


Frequency	50/60 Hz
Nominal voltage	220-240 V AC
DC input voltage	Yes, see Appendix 3

### Mechanical Properties

Material housing	Aluminium
Optical material	Polycarbonate

### Ambient Conditions

Operating temperature	-10 ~ 45 °C
Application temperature	25 °C
Storage environment	-25 ~ 50 °C



## Dimensional Drawing (mm)

LEDLima L12



LEDLima L15

