















- Modern design desk lamp with comfortable light
- Touch-button control for dimming and CCT-change
- Professional anti-glare, honeycomb lens
- Indirect background lighting for increased comfort
- Various scenes/features to enhance ease of use

Specifications

| Item Code | Item Description | Equivalent to (W) | Power (W) | Lumen | Efficacy (lm/W) | | Weight (kg/pc) |
|--------------|----------------------------------|----------------------|--------------|-------|--------------------|----------------|----------------|
| Dimmable | | | | | | | |
| 523003011600 | LEDSparrow-E 15W-DIM-830/840/850 | Halogen 125W | 15 | 1000 | 66 | 3000/4000/5000 | 0.70 |

Storage environment

| Technical Specifications | | | |
|------------------------------|-----------|--|--|
| Lifetime (L70) | 50,000 h | | |
| Lifetime (L80) | 30,000 h | | |
| On-/Off-cycles | 100,000 | | |
| Colour consistency (SDCM) | 4 | | |
| Dimmability | Touch Dim | | |
| Beam angle | 140° | | |
| Finishing | White | | |
| Colour rendering index (CRI) | > 80 | | |
| Degree of protection (IP) | IP20 | | |
| Impact strength | IK03 | | |
| Protection class | II | | |
| Risk group (EN 62471) | RG0 | | |
| With control gear | Yes | | |
| Glow wire test | 650°C | | |
| Power factor | ≥ 0.9 | | |
| | | | |

| Electrical Supply | | | | | |
|-------------------|-----------|--|--|--|--|
| Frequency | 50/60 Hz | | | | |
| Nominal voltage | 220~240 V | | | | |
| DC input voltage | No | | | | |
| 230V Cable length | 1.8 m | | | | |

| ABS | | | | | |
|--------------------|--|--|--|--|--|
| Polycarbonate | | | | | |
| | | | | | |
| Ambient Conditions | | | | | |
| -10~+45°C | | | | | |
| +25°C | | | | | |
| | | | | | |

-18~+50°C





Dimensional Drawing (mm)

LEDSparrow-E



